

UT692/693 SERIES

Optical Power Meters/Optical Multimeter (Power Meter & VFL)

- Low battery indication
- Auto power off
- IP65/2m drop proof
- Flashlight

Applications:

- Cable construction and maintenance
- Optical fiber communication
- Evaluation of optical equipment
- Production, installation, operation and maintenance of fiber optic transmission systems
- Optical engineering, production plant or facility maintenance



● UT692G

	Description	UT692D	UT692G	UT693D
Certificates	CE, RoHS			
Optical power meter				
Wavelength range	800nm~1700nm			
Calibrated wavelength	850nm, 980nm, 1300nm, 1310nm, 1490nm, 1550nm, 1625nm, 1650nm			
Measurement range	UT692D/UT693D: -70~10dBm, UT692G: -50~26dBm			
Uncertainty	±5%	√	√	√
Display resolution	Linear: 0.1%, logarithmic: 0.01dBm			
Connector	FC (optional: SC/ST)			
Detector type	InGaAs			
Visual fault locator				
Wavelength	650nm±10nm			
Power	10mW (measurable optical fiber length: approximately 8~10km)			
Mode	Continuous/pulse			
Connector	2.5mm universal connector			√
Power	1.5V battery (LR6) x 3			
Display	63mm x 40mm			
Product net weight	300g			
Product size	189mm x 87mm x 45mm			
Standard accessory	Batteries, English manual			
Standard individual packing	Gift box, carrying bag			
Standard quantity per carton	10pcs			
Standard carton measurement	295mm x 250mm x 210mm			
Standard carton gross weight	5.66kg			