

CON30

Conductivity Tester

(Conductivity / TDS / Salinity)



Precision easy operation: all functions operated in one hand.

Large LCD with backlight, Multi-line display for easy reading, Auto-Power Off saves battery after 5 mins non-use.

1*1.5V AAA long battery life

Easy maintenance, simple to change battery and electrode

Floats on water, IP67 rated

Field throw measurement (Auto Lock Function)



CON30 is the best value salt meter in your pocket, with 3 parameters (Conductivity / TDS / Salinity tester) in one and easy calibration. This dip-style tester is ideal for spot checking with greater flexibility.

Package Sets



CLEAN CON30 Conductivity Tester

- Broad measuring range: 0.0 $\mu\text{S}/\text{cm}$ - 20.00 mS/cm , from pure water to waste water applications.
- 4 parameters in one meter, simple calibration.

Range	0.0 $\mu\text{S}/\text{cm}$ (ppm) - 20.00 mS/cm (ppt)
Resolution	0.1 $\mu\text{S}/\text{cm}$ (ppm) - 0.01 mS/cm (ppt)
Accuracy	$\pm 2\%$ F.S.
Temp. Range	0 - 100.0 $^{\circ}\text{C}$ / 32 - 212 $^{\circ}\text{F}$
Working Temperature	0 - 60.0 $^{\circ}\text{C}$ / 32 - 140 $^{\circ}\text{F}$
Auto Temp. Compensation	0 - 60 $^{\circ}\text{C}$
Calibration	1 or 2 point auto calibrate (0% zero oxygen or 100% in air)
TDS Range	0.0 mg/L (ppm) - 20.00 g/L (ppt)
TDS Coefficient	0.40 - 1.00 Adjustable (Coefficient:0.5)
Salinity Range	0.0 mg/L (ppm) - 13.00 g/L (ppt)
Salinity Coefficient	0.65
Atmospheric:	
Pressure Compensation	600 - 1100 mbar
Auto backlight off	1 minutes
Auto power off	5 minutes without key be pressed
Power	1x1.5V AAA battery
Dimensions	(H×W×D) 185×40×48 mm
Weight	95g
Protection	IP67



www.cleaninst.com
Water Analysis Solutions