



The six models of the new 9915, 9916, 9917, 9917T, 9918 and 9918T series are the new 4000 counts multimeters. They set the standard with a combination of precision, features, easy-to-use, safety and reliability.

9917T/9918T have True RMS AC Voltage, Current readings, MAX-MIN recording, Peak recording, as well as Frequency and Capacitance ranges.

IP67 dust and water proof

True RMS (9917T/9918T)

Safety Conformance

- EN61010-1 CAT IV 600V, CAT III 1000V
- 1000V input protection on all ranges
- 10A/1000V & 0.5A/1000V fuses protection on current ranges



EMC & LVD
EN: 61326
EN: 61010-1
EN: 61010-02-031



Features

	9915	9916	9917/9917T	9918/9918T
Digital display counts	4000	4000	4000	4000
True RMS measurement			9917T	9918T
Safety design	*	*	*	*
Relative zero	*	*	*	*
Data Hold	*	*	*	*
MAX/MIN recording mode				*
Auto Power Off	*	*	*	*
Peak capture mode				*
Wide capacitance range		20mF		*
Current DC/AC 40μA		*		*
Analog bargraph/segment				*

Specifications

Function	Max. Range	Basic Accuracy	9915	9916	9917/9917T	9918/9918T
Voltage DC	1000 V	±0.5%	*	*	*	*
Voltage AC	1000V	±0.8%	*	*	*	*
Current DC	10A	±1.2%	*	*	*	*
Current AC	10A	±1.8%	*	*	*	*
Resistance	40MΩ	±0.8%	*	*	*	*
Duty Cycle	99.9%	±1.2%	*	*	*	*
Frequency	10MHz	±1.5%	*	*	*	*
Capacitance	200μF/40mF	±3.0%	200μF	20mF	200μF	40mF
Temperature	760°C/1400°F	±3.0%			*	*
Diode Check			*	*	*	*
Continuity Test			*	*	*	*

Size(HxWxD): 182mm x 82mm x 55mm

Weight: 360g

Accessories:

Test leads and 9V battery,

Type K temperature probe (9917/9918/9917T/9918T), gift box with carrying case.



Model 9918



Model 9917



Model 9915