



TES 1386 / 1387 TURBIDITY METER

FEATURES:

- ❖ Auto-Ranging from 0 to 1000 NTU.
- ❖ Waterproof and dustproof with IP67-rated housing that floats.
- ❖ Meets performance criteria as specified by ISO 7027 (DIN EN 27027) method.
- ❖ Compliant with ASTM D-6855-03 (EPA recognized)
- ❖ Four-point push-button calibration for full range accuracy.
- ❖ Manual data memory and read function.
- ❖ Auto data logger function. (1387)
- ❖ USB Interface. (1387)

Min Turbidity	0.1
Max Turbidity	1000
Turbidity Resolution	0.01, 0.1, or 1 NTU
Turbidity Accuracy	2% of readings
Data memory capacity	99 set (Direct reading from LCD display)
Data logger capacity	Micro SD CARD 4 GB (1387)
Min Temperature	0°C / 32°F
Max Temperature	50°C / 122°F
Waterproof	IP67
Battery	4 x AAA batteries
Size	148mm x 78mm x 64mm
Accessories	Carrying case, 10 – mL silicone oil, Lint – free cloth, four standard solution, four standard cuvettes, 4 AAA batteries, CD Software (1387), micro – USB Cable (1387)

www.MetroTIK.com

02133992447

02177335772

09129305772

MetroTik
گروه فنی و مهندسی

TES