

TES-1340 Hot-Wire Anemometer



FEATURES

- Fast Response Probe.
- Air Flow Volume
- Instant / Avg / 2/3 Vmax Flow Measurement.
- Velocity m/s, ft/min, knots, km/hr, mph.
- Data hold & Maximum / Minimum function.
- Manual data memory and read function (10 x 99 sets).
- LCD triple display.
- Auto power off function ON / OFF Time setting.
- Backlight function ON / OFF Time setting.
- Snake telescoping probe.



SPECIFICATION

i@	Measuring Range	Resolution	Accuracy
Air Flow	0.1 to 30.0 m/s	0.01 m/s _{i@}	±3% of reading ±1% FS
	0.2 to 110 km/hr	0.1 km/hr	
	10 to 6000 ft/min	1 ft/min	
	0.1 to 59 knots	0.01 knots	
	0.12 to 68 MPH	0.01 MPH	
Air Flow Volume	0 to 999900 CFM	0.001 CFM	
	0 to 999900 CMM	0.001 CMM	

Response time	1 second
Manual Memory Capacity	10 x 99 sets. (Direct reading from LCD display)
Operating Conditions	0°CXC ~ 50°CXC (32°CXF ~ 122°CXF), ±80% R.H.
Power Source	6 pcs size AAA Battery
Battery Life	Approx. 10 hours
Size	135(L) x 72(W) x 31(H)mm
Weight	Approx. 400g (including Probe)
Accessories	Instruction manual, Battery, Carrying case

i@

TES TES Electrical Electronic Corp.

Office: 7F, No. 31, Lane 513, Rui Guang Road, Neihu Dist., Taipei, Taiwan, R.O.C
 TEL:886-2-2799-3660 FAX:886-2-2799-5099
 E-Mail: tes@ms9.hinet.net