

TES-1260 Humidity Temperature Meter



FEATURES

- Dual LCD display.
- Dew Point Reading.
- Wet bulb Reading.
- MAX/MIN with Time Stamp.
- Data Hold function.
- °C & °F Switchable.
- DATA memory and read function (99 readings from LCD display)
- Auto Power Off.



SPECIFICATION

Measuring Range	Temperature : -20°C ~ 60°C (-4°F ~ 140°F) Humidity : 1%RH ~ 99%RH
Resolution	0.1°C / 0.1°F / 0.1%RH
Accuracy	Temperature : ±0.5°C, ±0.9°F Humidity : ±3%RH (at 25°C, 30 ~ 99%RH) ±5%RH (at 25°C, 1 ~ 30%RH)
Data Memory Capacity	Manual recording : 99 data sets (Direct reading from LCD display.)
Sampling Rate	2 times/sec
Operating Conditions	0°C ~ 60°C (32°F ~ 140°F) below 99% R.H. (no condensation)
Power Source	9V Battery
Battery Life	Approx. 200 hours
Size & Weight	193mm(L) × 59mm(W) × 26mm(H) / 140g
Accessories	Instruction manual, Battery.

Close Window



TES Electrical Electronic Corp.

Office:7F, NO.31, Lane 513,Rui Guang Road, Neihu Dist., Taipei, Taiwan, R.O.C.

TEL:886-2-2799-3660 FAX:886-2-2799-5099

E-Mail:tes@ms9.hinet.net